


5013 Max. 3 W
AC/DC PLUG-IN ADAPTER REGULATED


- Max. 3 W output power
- 230 VAC input voltage
- Compliance with relevant worldwide safety standards
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



| <u>Technical specifications</u> | |
|--|-----------------------------|
| <i>Input voltage:</i> | 230 VAC ± 10% 50 Hz |
| <i>Temperature range:</i> | -10°C to +40°C |
| <i>Protection:</i> | Thermal fuse in transformer |
| <i>Insulation class</i> | II |
| <i>Electrical safety</i> | EN 60950 |
| <i>EMC, Emission</i> | EN 61000-6-3 |
| <i>EMC, Immunity</i> | EN 61000-6-1 |
| <i>Mains connections:</i> | EU |
| <i>Output terminals:</i> | Secondary cable |
| <i>Dimensions EU (LxWxH):</i> | 56x44x37mm (without plug) |
| <i>Weight:</i> | EU: 200g |

Survey of Voltage versions

| <i>Output Voltage (VDC)</i> | <i>Load current (mA)</i> | <i>Output power (W)</i> |
|-----------------------------|--------------------------|-------------------------|
| 4,5 | 300 | 1,35 |
| 6 | 300 | 1,8 |
| 7,5 | 250 | 1,9 |
| 9 | 250 | 2,25 |
| 12 | 250 | 3 |