

## 4 Channels Serial to Fiber multiplexer

### MWF204-F



- ◆ RS232/RS422/RS485 conversion, full/half-duplex communication;
- ◆ Signal flow is automatically identified and transparently transmitted;
- ◆ Imported optical transceiver module to ensure the transmission distance;
- ◆ Unique serial protection circuit, hot-swappable;
- ◆ Industrial grade design and all surface mount processes ensure long-term reliability of the product.

### Product Description

MWF204 multi-channel serial to Fiber multiplexer can realize multi-channel RS-232/RS-485/RS-422 transmission on one optical fiber, which not only saves fiber resources, but also uses optical fiber as transmission medium, which has isolated high voltage and anti-electromagnetic Interference, anti-lightning and other advantages. It is widely used in various industrial control and industrial automation fields, and is particularly suitable for power system automation, traffic control and other departments.

Technical Specification	
<b>Technical parameters</b>	
Standard	Compliant with EIA RS-232, RS-485, RS-422
<b>Interface</b>	
Interface form	Serial Port: Electrical characteristics, Meet RS-232/RS-422/RS-485 Physical characteristics, Industrial terminal block Optical interface: Single multi-mode optional, SC/ST/FC optional
<b>Communication rate</b>	
Baud Rate	300bps~115.2Kbps, rate adaptive signal
<b>LEDs</b>	
Power indicator	POW
Data transmission indicator light	TXD, RXD, TX1-TX4, RX1-RX4, ERR (MWF204)
<b>Power</b>	
Power Supply	DC5~12V
Interface	BNC coaxial input
Power	<5W
Overload protection	Support
Lightning protection	600W/ms anti-lightning strike
Static protection	15kv antistatic
<b>Physical Characteristics</b>	
Shell	Aluminum housing
Dimension	225mm×30mm×96mm (Length × height × width) (MWF208)
Weight	0.4kg (MWF204)
<b>Transmission distance</b>	
Serial port line	RS-232, 15m@9600bps RS-422/RS-485, 1.2km@9600bps
Multimode fiber	1310nm, 5km
Single mode fiber	1310nm, 20km/40km 1310nm, 60km/80km
<b>Working Environment</b>	

## 4 Channels Serial to Fiber multiplexer

---

Operating Temperature	-40°C~85°C
Storage temperature	-40°C~85°C
Ambient Humidity	5%~95%
<b>Warranty</b>	
Warranty	5 Years
<b>Certification</b>	
Certification	CE, FCC

### Product Ordering Information

<b>Ordering Information</b>	
MWF204-F	4 ports RS232/RS485/RS422, 1 single/multimode optical port, SC/ST/FC available, desktop installation