


5117

Max. 4 W

AC/DC PLUG-IN ADAPTER REGULATED

- Max. 4 W output power
- 230 VAC input voltage
- Available with EU or UK terminals
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



| <u>Technical specifications</u> | |
|--|--|
| <i>Input voltage:</i> | 230 VAC ± 10% , 50 Hz |
| <i>Output voltage:</i> | 5 VDC ± 5% |
| <i>Max.output power:</i> | 4 W |
| <i>Max. load current:</i> | 800 mA |
| <i>Temperature range:</i> | 0°C to +40°C |
| <i>Protection:</i> | Thermal fuse in primary. Thermal overload protection and current limiting in regulator |
| <i>Insulation class</i> | II |
| <i>Electrical safety</i> | EN 60950 |
| <i>EMC, Emission</i> | EN 61000-6-3 |
| <i>EMC, Immunity</i> | EN 61000-6-1 |
| <i>Mains connections:</i> | EU or UK |
| <i>Output terminals:</i> | Secondary cable w/snap-on plugs |
| <i>Dimensions (LxWxH): EU</i> | 78x58x48mm |
| <i>Dimensions (LxWxH): UK</i> | 82x57x49mm |
| <i>Weight:</i> | 480g |