

20-Port Full Gigabit Industrial Ethernet Switch

MISCOM8220-4GF-16GT



- ◆ 4 Gigabit SFP port+16 10/100/1000BaseT(x)
- ◆ Support RIP/OSPF/PIM Layer 3 Routing Protocol
- ◆ Support MW-Ring/MSTP/VRRP/EAPS for network redundancy
- ◆ Support multiple management methods and network centralized management
- ◆ Single rib type fanless design
- ◆ Industrial grade wide temperature design
- ◆ Support industrial grade dual power input backup

Product Description

MISCOM8220 layer-3 full Gigabit industrial Ethernet switch is embedded with 4 Gigabit SFP+ 16 10/100/1000T(x) port in industrial communication providing advanced performance from Maiwe. With 35mm din-rail mounted that support front and rear panel installation. It integrates Layer 2 switching software such as VLAN/multicast/QoS/MW-Ring, in addition,it supports static/ dynamic routing /multicast routing, and supports a user friendly web console interface for easy configuration,offer you optimum performance and availability for demanding industrial communication

Technical Specification

Software performance	
Switch Function	Support VLAN Support GVRP Support port aggregation. Support flow control. Support Rate limit Support broadcast storm suppression.
Redundancy protocol	Support VRRP/EAPS Support MW-Ring and the recovery time<20 ms. Support RSTP/MSTP and compatible with STP
Multicast routing	Support IGMP snooping/ IGMP v1/v2/v3 Support GMRP Support static multicast Support PIM-SM/PIM-DM/PIM-DMv6
Unicast Routing	Support RIPv1/v2/RIPng/OSPFv1/v2 Support Static Routing Support PIM-SM/PIM-DM
Service quality management	Support ACL and L2-L4 data Filter Support SP/ WRR queuing
IP management	Support DHCP server/relay/client
Management and maintenance	Support Console/Telnet/and Web management methods/RMON Support SNMPv1/v2c Support FTP/TFTP file transfer and software update Support power failure alarm/power alarm/ port linkdown alarm/ring alarm Support port mirroring/Syslog/ LLDP/ RTC/SNTPv4
Technical specifications	
Ethernet Standard	IEEE802.3-10BaseT IEEE802.3u-100BaseTX/100Base-FX IEEE802.3x-Flow Control IEEE802.3z-1000BaseLX IEEE802.3ab-1000BaseTX IEEE802.1ab IEEE802.1D-Spanning Tree Protocol IEEE802.1w-Rapid Spanning Tree Protoco IEEE802.1Q -VLAN Tagging IEEE802.1s Multiple Spanning TreeProtocol IEEE802.1p -Class of Service IEEE802.1X-Port Based Network Access Control GVRP/RIPv1/v2&OSPFv1/v2/v3/VRRP/DHCP/CLI/EAPS/Qos/LACP/LLD P/IGMP/PIM/SNMP/SNTP/SSH

Switch properties	
Priority queue	8
VLAN ID	1-4096
IGMP Groups	512
MAC table	16k
Switch Bandwidth	40Gbps
Route Table	8k
Switch Delay	<5 μ s
Interface	
Gigabit ports	Port numbers:20
	Connector:SFP for fiber port(LC,single or multi mode),RJ45 for copper port
	Baud rate:1000Base-LX(fiber port), 10/100/1000M for copper port
Console port	RS232/RJ45
Terminal block for power input	5.08mm terminal block
Terminal block for relay alarm	5.08mm terminal block,1A@24VDC
Communication distance	
Twisted-pair	100m(CAT5/CAT5e cable)
Multimode fiber	Gigabit multi mode: 850nm 550m
Single mode fiber	Gigabit single mode: 1310nm 20km
LED indicator lights	
Front panel LED	Port light: LINK/ACT;SPEED
	Running light: RUN
	Power LED: PWR1/PWR2
	Alarm LED: AIARM
Power Requirements	
Power input	Standard DC24 dual power supply:DC48V dual power/ AC/DC220V(85-264VAC/110-370VDC) sing power available
Full-load consumption	<15W
Overload protection	support
Inversed protection	support

Redundancy protection	support
Working Environment	
Operating Temperature	-40°C~70°C
Storage temperature	-40°C~85°C
Ambient Humidity	5%~95%(non-condensing)
Physical Characteristics	
Shell	IP40 protection,aluminium alloy shell
Installation	3.5" din rail-mounted installation
Dimension	156mmx137.7mmx85mm
Industry standard	
EMC	EN61000-4-2 (ESD) ,Level 4 EN61000-4-3 (RS) ,Level 4 EN61000-4-4 (EFT) ,Level 4 EN61000-4-5 (Surge) ,Level 4 EN61000-4-6 (CS) ,Level 4 EN61000-4-8,Level 5
Impact	IEC60068-2-27
Falling	IEC60068-2-32
Shock	IEC60068-2-6
Warranty	
Warranty period	5 Years
Certification	CE,FCC,RoHS

Product Ordering Information

Warranty	
MISCOM8220G-4G F-16GT-DC24	4xGigabit SFP+16x10/100/1000baseT(x), standard dual power supply
MISCOM8220G-4G F-16GT-AD220	4xGigabit SFP+16x10/100/1000baseT(x), standard single power supply