

DOM-48D15S3.3

Input	Input Voltage	DC 36V~60V	
	Start-up Voltage	36V	
	Input Frequency	/	
	Input Current	0.5A @36VDC	
	Inrush Current	/	
Output	Output 1	Voltage	3.3V
		Current	3A
		Output Accuracy	±3%
		Ripple and Noise	<50mV
	Output Power	10	
	Efficiency	65%typ @48VDC IN	
	Output Voltage Adjust Range	3.29V~3.5V	
	Start-up Time	<1S @48VDC IN, Io=100%	
	Hold-up Time	/	
	Power Factor	/	
	Protection Function	Over Voltage Protection	/
Over Current Protection		/	
Short Circuit Protection		Pulsing mode	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VAC/1min	
	I/P-F/G Primary-PG	/	
	O/P-F/G Secondary-PG	/	

Isolation Resistance	I/P-O/P Primary-Secondary	≥50MΩ @500VDC	
	I/P-F/G Primary-PG	/	
	O/P-F/G Secondary-PG	/	
Leakage Current		/	
Safety Standards		/	
Harmonic Current		/	
EMC	EMI	Conducted Interference	GB 9254 CLASSA; CISPR 22 Class A
		Radition Disturbance	GB 9254 CLASSA; CISPR 22 Class A
	EMS	EFT	GB/T 17626.4LEVEL3; IEC 61000-4-4 Level 3
		Lightning Surge	GB/T 17626.5LEVEL3; IEC 61000-4-5 Level 3
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. & Humidity	-25 ~85 /10%~95%RH(Non condensing)	
Structure	Size(mm)	Length100 X Width46 X Height28	
product F.G. PartNUM		015200001003	
Testing Item Explain			
Product Picture			