

## DOM-48D40D30+5

Input	Input Voltage	DC 40V~60V	
	Start-up Voltage	40V	
	Input Frequency	/	
	Input Current	/	
	Inrush Current	/	
Output	Output 1	Voltage	30V
		Current	1A
		Output Accuracy	±5%
		Ripple and Noise	<100mV
	Output 2	Voltage	5V
		Current	1A
		Output Accuracy	4.85V~5.4V
		Ripple and Noise	<50mV
	Output Power	35	
	Efficiency	80%typ @48VDC IN	
	Output Voltage Adjust Range	/	
	Start-up Time	<1S @48VDC IN, Io=100%	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	V1:33.5V~36V	
	Over Current Protection	V1:1.2A~1.6A, pulsing mode	
	Short Circuit Protection	pulsing mode	

Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VDC/1min	
	I/P-F/G Primary-PG	500VDC/1min	
	O/P-F/G Secondary-PG	500VDC/1min	
Isolation Resistance	I/P-O/P Primary-Secondary	/	
	I/P-F/G Primary-PG	/	
	O/P-F/G Secondary-PG	/	
Leakage Current		/	
Safety Standards		/	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature		0 ~45 /20%~90%RH(Non condensing)
	Storage Temp. & Humidity		-25 ~85 /10%~95%RH(Non condensing)
Structure	Size(mm)		Length127 X Width76 X Height27
product F.G. PartNUM		015200000014	
Testing Item Explain			

Product Picture

