

DOM-48D40T5+12R+24

Input	Input Voltage	DC 36V~60V	
	Start-up Voltage	48V	
	Input Frequency	/	
	Input Current	<0.35A	
	Inrush Current	/	
Output	Output 1	Voltage	5V
		Current	3A
		Output Accuracy	±3%
		Ripple and Noise	<100mV
	Output 2	Voltage	12V
		Current	1A
		Output Accuracy	
		Ripple and Noise	
	Output 3	Voltage	24V
		Current	0.2A
		Output Accuracy	
		Ripple and Noise	
	Output Power	30	
	Efficiency	70%typ	
	Output Voltage Adjust Range	/	
	Start-up Time	>1.0s	
	Hold-up Time	>20ms	
	Power Factor	/	

Protection Function	Over Voltage Protection	115%~150% block mode	
	Over Current Protection	105%~150% recovers automatically	
	Short Circuit Protection	long term, recovers automatically	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	3000VAC/min;10mA	
	I/P-F/G Primary-PG	1500VAC/min;10mA	
	O/P-F/G Secondary-PG	500VAC/min;10mA	
Isolation Resistance	I/P-O/P Primary-Secondary	≥50M	
	I/P-F/G Primary-PG	≥50M	
	O/P-F/G Secondary-PG	≥50M	
Leakage Current		/	
Safety Standards		/	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%	
	Storage Temp. & Humidity	-25 ~85 /10%~95%	
Structure	Size(mm)	Length127 X Width76 X Height32	
product F.G. PartNUM		015200000011	

Testing Item Explain

Product Picture

