

小型化开关电源

Mini size power supply



35W 单路输出
35W Single output

Approvals:CE

Size:99mm×82mm×36mm

全范围电压输入 通电LED指示灯 过载/过压/短路保护 100%老化测试 2 年质保	Universal AC input/ full range Power on indication Overload /Over voltage /Short Circuit Protection 100% full load burn-in test Two years warranty
AC输入电压	AC input voltage
电压88~264VAC 常规100-240VAC	88~264VAC Nominal 100-240VAC
输入频率	Input frequency
47~63Hz	47~63Hz
冲击电流	Inrush current
40A@230VAC, 全载冷态	40A @230VAC full load cold start
维持时间	hold up time
80ms@230 VAC 全载	80ms@230 VAC
过载保护	Overload protection
110%- 150%	100% of rated maximum load
过压保护	Over voltage protection
110%-140%	110%-150%
工作温度	Working temperature
-10 to 50°C	-10 ~ 50°C
安全标准	Safety standard
UL60950-1	UL60950-1
EMC标准	EMC standard
EN55022 class B	EN55022 class B
MTBF	MTBF
10 ⁵ h at 25°C	10 ⁵ h at 25°C
耐压标准	Withstand Voltage
I/P-O/P:3KV,1min I/P-FG:1.5KV,1min	I/P-O/P:3KV I/P-FG:1.5KV,1min
重量	Weight
0.2Kg/pcs	0.2Kg/pcs

P/N 产品型号	Output 输出	Tol. 容差	R&N 纹波&噪声	Effi. 效率	LoadRegulation 负载调整率	Line Regulation 线性调整率
ESPR-35-3.3	3.3V,7A	3%	80mV	73%	3%	3%
ESPR-35-5	5V,7A	2%	80mV	77%	2%	2%
ESPR-35-12	12V,3A	1%	120mV	81%	1%	1%
ESPR-35-24	24V,1.5A	1%	120mV	84%	1%	1%
ESPR-35-48	48V,0.8A	1%	200mV	84%	1%	1%