

小型化开关电源

Mini size power supply

75W 单路输出
75W Single output



Approvals:CE

Size:129mm×97mm×38mm

全范围电压输入 通电LED指示灯 过载/过压/短路保护 100%老化测试 2 年质保	Universal AC input/ full range Power on indication Overload /Over voltage /Short Circuit Protection 100% full load burn-in test Two years warranty
AC输入电压 88~264VAC 常规100-240VAC	AC input voltage 88~264VAC Nominal 100-240VAC
输入频率 47~63Hz	Input frequency 47~63Hz
冲击电流 40A@230VAC, 全载,冷态	Inrush current 40A @230VAC
维持时间 60ms@230 VAC 全载	hold up time full load cold start 60ms@230 VAC
过载保护 110%~150%	Overload protection 100% of rated maximum load 110%- 150%
过压保护 110%~140%	Over voltage protection 110%-140%
工作温度 -10 to 50°C	Working temperature -10 to 50°C
安全标准 UL60950-1	Safety standard UL60950-1
EMC标准 EN55022 class B	EMC standard EN55022 class B
MTBF 10 ⁵ h at 25°C	MTBF 10 ⁵ h at 25°C
耐压标准 I/P-O/P:3KV,1min I/P-FG:1.5KV,1min	Withstand Voltage I/P-O/P:3KV I/P-FG:1.5KV,1min
重 量 0.41Kg/pcs	Weight 0.41Kg/pcs

产品型号 P/N	输出 Output	容差 Tol.	纹波&噪声 R&N	效率 Effi.	负载调整率 LoadRegulation	线性调整率 Line Regulation
ESPR-75-3.3	3.3V,15A	3%	80mV	71%	3%	3%
ESPR-75-5	5V,12A	2%	80mV	76%	2%	2%
ESPR-75-12	12V,6A	1%	120mV	81%	1%	1%
ESPR-75-24	24V,3.2A	1%	120mV	85%	1%	1%
ESPR-75-48	48V,1.6A	1%	200mV	86%	1%	1%