

15W Single Output M2 Series



- Universal AC input / full range
- Miniature size, high power density
- Top international brand components for key parts
- UL, CE approved (refer to spec. of each series)
- Protections: overload/ over voltage/ short circuit
- 5 years limited warranty
- F6015SEL 86 × 58.5 × 31.5(mm)

AC input voltage range	88~264VAC (124~370VDC)
Input frequency	47~63Hz
Inrush current	cold start, 15A/115V, 30A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Voltage adjust range	± 10%
Output overload protection	105~150%, hiccup mode, auto recovery,
Output over voltage protection	clamping by zenor diode
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temperature	-20℃~+70℃ (refer to the derating curve)
Safety standards	meet GB4943, UL60950, EN60950
EMC standards	meet GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection
Weight	0.14kg

Model	DC Output		Load regul.	R&N	Efficiency
HF15W-SML-5	5V	3.0A	0.5%	80mV	77%
HF15W-SML-12	12V	1.3A	0.5%	120mV	80%
HF15W-SML-24	24V	0.7A	0.5%	150mV	82%
HF15W-SML-48	48V	0.35A	0.5%	150mV	82%