


40W Single Output Series - with approval



- High reliability
- Universal AC input / full range
- Approvals: UL, ETS/EMC/ CE
- 100% full load burn-in test
- Protections: overload/over voltage/short circuit
- 2 years warranty
- F603 129 x 98 x 40(mm)



AC input voltage range	85~264VAC
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	± 0.5%
Output voltage adjust range	± 10%
Output overload protection	110~150%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10 ~+50 , 20%~93%RH (non condensing)
Storage temp. & humidity	-20 ~+85 , 20%~95%RH (non condensing)
Safety standards	GB4943, UL60950, EN60950
EMC standards	GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
HF40W-SL-5	5V	8.0A	0.5%	80mV	72%
HF40W-SL-12	12V	3.5A	0.5%	100mV	76%
HF40W-SL-15	15V	2.8A	0.5%	100mV	76%
HF40W-SL-24	24V	1.8A	0.5%	100mV	78%
HF40W-SL-48	48V	0.9A	0.5%	150mV	80%

*Note: Max.V=48, Max.A=8, Max.VA=40

Drawing

