


60W Dual Output Series - with approval



- High reliability
- Universal AC input / full range
- Approvals: ETS/EMC/ CE
- 100% full load burn-in test
- Protections: overload/over voltage/short circuit
- V1 is isolated from the other output
- 2 years warranty
- F605 160 x 98 x 39(mm)

AC input voltage range	85~264VAC		
Inrush current	cold start, 20A/115V, 40A/230V		
Input leakage current	< 0.7mA/ 230VAC		
Line regulation (full load)	± 0.5%		
Load regulation	V ₁ : ± 0.5%, V ₂ : ± 1% (with regulator); ± 6% (without)		
Output voltage adjust range	V ₁ : ± 5% of rated output voltage		
Output overload protection	110~150%		
Output over voltage protection	115~150%		
Withstand voltage	I/P-O/P: 3.0KVAC/1min; I/P-F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min		
Rise, Hold up time	50ms, 20ms@full load (typical)		
Operating temp. & humidity	-10 ~+50 , 20%~93%RH (non condensing)		
Storage temp. & humidity	-20 ~+85 , 20%~95%RH (non condensing)		
Safety standards	GB4943, UL60950, EN60950		
EMC standards	GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11		
Cooling method	convection		
Model	DC Output	R&N	Efficiency
HF60W-DL-A	5V	0.5~6.0A	80mV
	12V	0.2~4.0A	150mV
HF60W-DL-B	5V	0.3~6.0A	80mV
	24V	0.0~2.0A	100mV
HF60W-DL-C	12V	0.3~4.0A	100mV
	12V	0.2~3.0A	120mV
HF60W-DL-D	15V	0.3~3.0A	100mV
	15V	0.2~2.5A	150mV

Drawing

