

75W Single Output M2 Series



CE

- Universal AC input / full range
- Miniature size, high power density
- Top international brand components for key parts
- UL, CE approved (refer to spec. of each series)
- Protections: overload/ over voltage/ short circuit
- 5 years limited warranty
- F603 129 × 98 × 40(mm)

AC input voltage range	88~264VAC (124~370VDC)
Input frequency	47~63Hz
Inrush current	cold start, 20A/115V, 40A/230V
Input leakage current	< 1mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Voltage adjust range	± 10%
Output overload protection	105~130%, hiccup mode, auto recovery
Output over voltage protection	115~150%, shut off, re-power on to recover
Withstand voltage	I/P -O/P: 3.0KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temperature	-20°C ~+70°C (refer to the derating curve)
Safety standards	meet GB4943, UL60950, EN60950
EMC standards	meet GB9254, EN55022 classB, EN55024 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection
Weight & packing	0.42kg, 42pcs/ CTN

Model	DC Output		Load regul.	R&N	Efficiency
HF75W-SSM-5	5V	12.0A	0.5%	80mV	73%
HF75W-SSM-12	12V	6.0A	0.5%	120mV	82%
HF75W-SSM-15	15V	5.0A	0.5%	120mV	82%
HF75W-SSM-24	24V	3.2A	0.5%	150mV	84%
HF75W-SSM-48	48V	1.6A	0.5%	150mV	85%

Drawing

