

# NR500 Standard Series Industrial Cellular VPN Router

## PRODUCT OVERVIEW

### Industrial internet access

- Wireless Mobile Broadband 2G / 3G / 4G Connection
- Remote access to SCADA System for Industrial Automation
- Reduce high costs for on-site maintenance

### Designed for industrial usage

- Power Input Range 9 to 48 VDC
- Industrial designed for harsh environment
- Compact metal casing for easy mounting

### Secure and reliable remote connection


- Connection manager ensure seamless communication
- Support Multiple VPN tunnels for data encryption
- Firewall prevents unsafe and unauthorized access

### Easy to use and easy maintenance

- User-friendly web interface for human interaction
- Easy configuration for deployment
- Support 3rd Party remote management cloud



## TYPICAL APPLICATION



# SPECIFICATION

CELLULAR	
Frequency Bands	<b>4G(LTE)</b> <b>AU&amp;NZ:</b> B1/B2/B3/B4/B5/B7/B28, B40 <b>EMEA:</b> B1/B3/B5/B7/B8/B20, B38/B40/B41 <b>America:</b> B2/B4/B12/B13 <b>Japan:</b> B1/B3/B8/B18/B19/B26, B41 <b>China:</b> B1/B3/B8, B34/B38/B39/B40/B41  <b>WCDMA:</b> B1/B2/B4/B5/B8/B19 <b>TD-SCDMA:</b> B34/B39  <b>GSM/EDGE:</b> B2/B3/B5/B8 <b>More Bands Demands please contact with us</b>
SIM	2 x SIM slots, 1.8V / 3V
SIM Failover	Auto-switch cases: weak signal, data limited, SMS limited, no network, network denied, data connection fail
Auto APN List	Operator APN list
Mobile Quota Control	Set up customized data limits for both SIM cards
Number of Antennas	2 (MAIN + AUX)
Connector	SMA female

ETHERNET	
Number of Ports	1 x WAN + 1 x LAN or 2 x LAN
Port Type	Auto 10/100 Mbps, auto MDI/MDIX
Magnet Isolation Protection	1.5 KV

Wi-Fi (Optional)	
Wireless Mode	IEEE 802.11b/g/n, Access Point (AP), Client
Wireless Speed	2*2 MIMO, 300 Mbps
Wireless Security	WPA, WPA2, WEP, 64/128 AES, TKIP
Frequency Bands	2.412 - 2.484 GHz (2.4 GHz ISM band)
Antennas	2 x RP-SMA for Wi-Fi antenna connectors

SERIAL	
Number of Ports	1 x RS-232 (3 PIN) + 1 x RS-485
Connector	Terminal block
ESD Protection	± 15 KV
Band Rate	300bps to 115200bps

DIGITAL INPUT & OUTPUT	
Type	2 x DI + 2 x DO
Connector	Terminal block
Isolation	3KVDC or 2KVrms
Absolute maximum VDC	36VDC
Absolute maximum ADC	100 mA

## ORDERING INFORMATION

Model	Part Number	Description
NR500-S4G	A502433	4G LTE, Dual SIMs, 2 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC
	A512433	4G LTE, Dual SIMs, 2 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC, 2.4GHz Wi-Fi
NR500-S3G	A502333	3G, Dual SIMs, 2 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC
	A512333	3G, Dual SIMs, 2 x Eth, 1 x RS232 (3 PIN), 1 x RS485, 2 x DI, 2 x DO, 9 - 48VDC, 2.4GHz Wi-Fi

NETWORK	
Routing	Static routing
Network Protocols	TCP, UDP, IPv4, ICMP, NTP, DNS, HTTP, HTTPS, ARP, PPP, PPPoE, DHCP
Connection Manager	Ping Detection, Timer Reboot, ICMP for link detection
DHCP	Static and dynamic IP allocation
DDNS	Supported some service providers, others can be configured manually
Network Backup	Cellular, Wired and Wi-Fi WAN options, each of which can be used as backup
Firewall	Flexible access control of TCP, UDP, ICMP packets, MAC address filter

VPN	
OpenVPN	Multiple clients and server can be running simultaneously
IPsec	IKEv1, IKEv2, supports up to 3 x VPN IPsec tunnels
DMVPN (Pending)	Dynamic Multipoint Virtual Private Networking DMVPN

MONITORING & MANAGEMENT	
Web GUI	HTTP/HTTPS, firmware upgrade
Command Line Interface	SSHv2 and TELNET
3rd party platform	Pending
SNMP (Pending)	SNMP (v1, v2, v3), SNMP trap

POWER	
Connector	3-pin 3.5 mm female socket with lock
Input Voltage Range	9 to 48 VDC
Power Consumption	Idle: 100 mA@12 V Data link: 400 mA (peak) @12 V

HARDWARE SPECIFICATION	
Watchdog	Built-in watchdog
LEDs	SYS, NET, USR, RSSI x 3
Reset Button	Reset/restore to factory default button
Ingress Protection	IP30
Housing & Weight	Metal, 300 g
Dimensions	106mm x 106mm x 40mm
Installations	DIN-rail mounting
Operating Temperature	-40 °C to 75 °C
Operating Humidity	5% to 95% non-condensing

APPROVAL		
EMI	EN 55032:2012 Class B	
EMS	IEC 61000-4-2 ESD:	Level 4
	IEC 61000-4-3 RS:	Level 3
	IEC 61000-4-4 EFT:	Level 3
	IEC 61000-4-5 Surge:	Level 3
	IEC 61000-4-6 CS:	Level 3
Vibration	EN50155	